



Good Cold



MOTOCOMPRESORES SEMI-HERMETICOS

BAJA TEMPERATURA R404A

HP (Potencia)	MODELO	Desplazamiento m³/hs	Carga Aceite cm³	Rendimiento Frigorífico (Kcal/h)								Volts / Nº f / Hz	Ø Succión	Ø Descarga	Peso Bruto Kg
				Temperatura Evaporación											
				-40°C	-35°C	-30°C	-25°C	-20°C	-15°C	-10°C	-5°C				
5	JCA2L50	22,5	2500		2580	3595	4764	6132	7387	9288	11498	380/50/3	1 1/8"	5/8"	96
7,5	JCA3R75	40,9	3000	2984	4265,6	5796	7611	9744				380/50/3	1 3/8"	1 1/8"	158
10	JCA3R100	49,9	3000	4549	6157,6	8058	10311	12969				380/50/3	1 3/8"	1 1/8"	165
15	JCA4V150	71	4500	5771	8187,2	11085	14439	18421	23022			380/50/3	1 5/8"	1 1/8"	208
30	JCCO30BT	129	7500		14800	19950	25886	32963	41125			380/50/3	2 1/8	1 3/8	230

BAJA TEMPERATURA



R22

HP (Potencia)	MODELO	Desplazamiento m³/hs	Carga Aceite cm³	Rendimiento Frigorífico (Kcal/h)								Volts / Nº f / Hz	Ø Succión	Ø Descarga	Peso Bruto Kg
				Temperatura Evaporación											
				-40°C	-35°C	-30°C	-25°C	-20°C	-15°C	-10°C	-5°C				
5	JCA2L50	22,5	2500	1604	2158,6	3165	4266	5642	7267	9150	11085	380/50/3	1 1/8"	5/8"	96
7,5	JCA3R75	40,9	3000	2236	3612	5246	7164	9520	12298	15824	19436	380/50/3	1 3/8"	1 1/8"	158
10	JCA3R100	49,9	3000	2924	4730	6966	9331	12040	15308	19178	23650	380/50/3	1 3/8"	1 1/8"	165
15	JCA4V150	71	4500	5272	7335,8	9950	13201	17217	22111	28036	35165	380/50/3	1 5/8"	1 1/8"	208



Temperatura Condensación: 50°C

 Forzador de cabeza



 Forzador de Cabeza + Dispositivo de Spray Liquido (Opcional)



	A	B	C	D	E
JCA2L50	482	340	370	280	295



	A	B	C	D	E
JCA3R75	705	356	470	305	381
JCA3R100	705	356	470	305	381



	A	B	C	D	E
JCA4V150	710	465	510	305	380
JCCO30BT	790	530	520	380	305



Good Cold